

DATA SHEET
FCB SERIES
 FLAT COPPER BRAID



| | |
|--------------------|-----------------------|
| DESCRIPTION | FLEXIBLE COPPER BRAID |
| SIZE (mm) | Various |
| COLOUR | TINNED BRAID |
| WEIGHT (kg) | Various |

MATERIAL: FLEXIBLE FLAT TINNED COPPER BRAID

HARDWARE: Not Applicable

TESTING:

SALES DRAWING No: TEMPLATE DRAWING

NOTE: The “FCB” Flexible Copper Braids are made from numbers of flat tinned braids. Ferrules are pressed on the end of the braid to form flat connection plates to bolt onto bus-bars or terminals.

All sizes are nominal values. All Braids can be covered with Heatshrink upon request, note this will derate the current carrying capacity

The “FCB” Flexible Copper Braids are available in two Braid Types:

- i) 150A – Stranding – 48/10/0.25mm, Nominal Cross Section Area – 25mm²
- ii) 210A – Stranding – 48/16/0.25mm, Nominal Cross Section Area – 39mm²

*****Custom made sizes available upon request*****
FILL OUT BRAID TEMPLATE IF YOU REQUIRE A
CUSTOM MADE SIZE.
MINIMUM ORDER QUANTITIES MAY APPLY